1402 WICKELSTAR II – FILM WRAPPER

METASA
CURVE. PRECISION. MASTERY.









The Wickel Star II film winder is impressively practical to use. With this efficient combination machine, you can unwind and rewind film. The hydraulic unwind brake is innovative and user-friendly. It can be activated via the control panel as required. The powerful hydraulic motor and optimally positioned ball bearings ensure smooth, vibration-free winding. The speed control helps to preserve the film and keep costs down. The sturdy frame construction, made from tubular and channel sections, guarantees safety and durability. The side lift is fitted with heavy-duty bearing guides and sufficient lubrication points; the two arms can be adjusted continuously. For standard winding tubes (1600 mm and 1750 mm), the side lift is up to 375 mm.

ARTICLE-NUMBER 1402

Weight*: ca. 550 kg
Dimensions*: 2500 x 1450 x 1550 mm (B x T x H)

- + UNWINDING AND WINDING
- + POWDER-COATED AND GALVANISED
- + SPEED CONTROL OF THE WINDING MOTOR
- + HYDRAULIC UNWINDING BRAKE
- + LABOUR-SAVING AND EFFICIENT
- + PROTECTS FILM, NETS AND NON-WOVEN FABRIC THANKS TO SMOOTH RUNNING MECHANISM
- + HYDRAULIC LATERAL LIFT UP TO 375 MM

SUITABLE FOR THE FOLLOWING CROPS

- Strawberries
- Vegetables
- Asparagus
- Onions

ART.-NR.	ADDITIONAL ARTICLE
1039	Winding tube Ø 88,9 mm x 1600 mm
1045.12	Complete film reel, 1200 mm, winding tube, 1750 mm
1045.05	Coiling tube, Ø 88.9 mm x 1,750 mm
1045.03	Split reel plate, 800 mm
1045.04	Split reel plate, 1000 mm
1402.02	Winding mechanism
1499	Front-loading adapter

METASA
METALLKONSTRUKTIONEN UND ERNTETECHNIK GMBH

Haldenstraße 14
45966 Gladbeck
Germany

T +49 2043 378363-0
info@metasa.de
www.metasa.de

*Bei angegebenen Daten, Gewichten und Maßen sind produktionsbedingte Toleranzen möglich. Aus diesen Informationen können keine rechtlich verbindlichen Zusicherungen bestimmter Eigenschaften abgeleitet werden. Irrtümer und Änderungen vorbehalten.

#1401 - 1401.01 | DATENBLATT JP | 02-2024 | V2.0