



The Metasa weeding frame from the ProfiStar series is designed specifically for mechanical weed control within and between crop rows. It can be combined with other implements from the ProfiStar series, such as the three-row row cultivator. The implement mounts are designed to KAT2/3 standards. The robust tubular frame construction is equipped with StVZO-compliant warning signs and ensures safe and stable operation. Six hardened disc blades (Ø460 mm) with anti-twist protection are height-adjustable and run precisely along the edges of the crop. Straw-covered aisles are effectively worked by nine staggered swallow-tail blades without pushing the straw aside. All tools can be continuously adjusted to any position on the beam. An integrated measurement scale facilitates precise adjustment. The cultivator frame is available in two-row, three-row, and four-row configurations.

ARTICLE-NUMBER 1459

weight*: ca. 680 kg
 dim.*: 3000 x 1300 x 1420 mm (B x T x H)

SUITABLE FOR THE FOLLOWING CROPS



Strawberries



Vegetables



Silphie

METASA

METALLKONSTRUKTIONEN UND ERNTE-TECHNIK GMBH

Haldenstraße 14
 45966 Gladbeck
 Germany

T +49 2043 378363-0
 info@metasa.de
 www.metasa.de

- + SUITABLE FOR GROUND AND RAISED-BED CULTIVATION
- + KAT2/3 SELECTED FOR RECORDING
- + LARGE 460 MM DISC HARROW
- + CAN BE MOUNTED ON THE FRONT OR REAR
- + NO ADDITIVES IN THE STRAW BEDDING
- + OPTION TO ATTACH TO COMBINATIONS
- + HEAVY CULTIVATOR HANDLE WITH GOOSEFOOT SHARES
- + TOOLS ARE INFINITELY ADJUSTABLE

ART.-NR. ADDITIONAL ARTICLES

1440	Sliding Frame
1450	ProfiStar 3-rows
1451	ProfiStar 2-rows
1459.01	3-row bending beam
1459.04	2-row bending beam
1459.06	Corrugated Disc Frame
1459.20	Finger hoe

*Bei angegebenen Daten, Gewichten und Maßen sind produktionsbedingte Toleranzen möglich. Aus diesen Informationen können keine rechtlich verbindlichen Zusicherungen bestimmter Eigenschaften abgeleitet werden. Irrtümer und Änderungen vorbehalten.